

Organization **TC2100 Bldg/Room PK2**

U. S. DEPARTMENT OF COMMERCE

COMMISSIONER FOR PATENTS


P.O. BOX 1450

ALEXANDRIA, VA 22313-1450

IF UNDELIVERABLE RETURN IN TEN DAYS

OFFICIAL BUSINESS

AN EQUAL OPPORTUNITY




GAO-135* 945393049 1A03 14 06/12/04

RETURN TO SENDER

GAO

**MOVED LEFT NO ADDRESS
UNABLE TO FORWARD
RETURN TO SENDER**





UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/916,253	07/30/2001	Yang Gao		8659

Yang Gao
41135 Canyon Heights Drive
Fremont, CA 94539

7590 06/08/2004

EXAMINER

COURTENAY III, ST JOHN

ART UNIT	PAPER NUMBER
----------	--------------

2126

DATE MAILED: 06/08/2004

4

Please find below and/or attached an Office communication concerning this application or proceeding.

RECEIVED

JUN 18 2004

Technology Center 2100

Sl

Office Action Summary	Application No.	Applicant(s)	
	09/916,253	GAO ET AL.	
	Examiner	Art Unit	
	St. John Courtenay III	2126	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 30 July 2001.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☒ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-8 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-8 is/are rejected.
- 7) ☒ Claim(s) 5-8 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.


Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 30 July 2001 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.


ST. JOHN COURTENAY III
PRIMARY EXAMINER

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

Detailed Action

1. Claims 5, 6, 7 and 8 are objected to under **37 CFR 1.75(c)** as being in improper form because a multiple dependent claim should refer to other claims in the alternative only. See **MPEP § 608.01(n)**. Accordingly, claims 6-8 have not been further treated on the merits. Claim 6 is objected to because claim 6 depends upon claim 5.

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1-6 are rejected under 35 U.S.C. 103(a) as being unpatentable over Applicant's Admitted Prior Art (**APA**) in view of **Goodman**, Danny, "Danny Goodman's JavaScript Handbook" IDG Books Worldwide, 1996, pages 32-35.

As per independent claim 1:

APA discloses the invention substantially as claimed:

APA teaches a method for executing an RPC (Remote Procedure Call) over HTTP from a Web page within the application window at a client device, the method comprising:

- containing, in the application window of a client device, at least one Web page [see discussion of NetGratus Remote Scripting, page 8 of instant specification];

- transmitting, to a server, an HTTP request initiated by a first HTML element [see discussion of NetGratus Remote Scripting, page 8 of instant specification];
- invoking, at a server, a procedure or a set of program code identified by the URL of said first HTML element [see discussion of NetGratus Remote Scripting, page 8 of instant specification];

However, **APA** does not *explicitly* teach receiving, at the Web browser from the server in the transmitting action, output of the procedure or program code in the invoking action into a second HTML <script> element. APA does teach that the client-side proxy uses <iframe> for Microsoft Internet Explorer browsers and <layer> for Netscape browsers as the vehicle to transport the data [see discussion of NetGratus Remote Scripting, page 8 of instant specification].

Goodman teaches the well known use of the <script> tag to mark sections of executable code [e.g., see "<SCRIPT> tag" discussion pages 32-35.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to improve upon the system taught by **APA** by using the <script> tag (instead of <iframe>) because it would provide **APA's** system with the enhanced capability of using client-side JavaScript code to process the data returned from the server after the remote procedure is executed.

As per dependent claim 2:

APA teaches the application window is a Web browser window [see discussion of NetGratus Remote Scripting, page 8 of instant specification].

As per dependent claim 3:

APA teaches the first HTML element in the transmitting action and the second HTML element in the receiving action are contained within the same Web page [see discussion of NetGratus Remote Scripting, page 8 of instant specification - APA does teach that the client-side proxy uses <iframe> for Microsoft Internet Explorer browsers and <layer> for Netscape browsers as the vehicle to transport the data].

As per dependent claim 4:

APA teaches the first HTML element in the transmitting action and the second HTML element in the receiving action are contained within different Web pages [see discussion of NetGratus Remote Scripting, page 8 of instant specification].

As per dependent claim 5:

APA, as modified by Goodman, teaches the first HTML element in the transmitting action is an HTML <script> element [see discussion of NetGratus Remote Scripting, page 8 of instant specification; see Goodman disclosure of the <script> element pages 32-35].

As per dependent claim 6:

APA, as modified by Goodman, teaches the first HTML element in the transmitting action is the same as the second HTML element in the receiving action. [APA teaches that the client-side proxy uses <iframe> for Microsoft Internet Explorer browsers and <layer> for Netscape browsers as the vehicle to transport the data; Goodman teaches the use of the <script> element, as discussed above in the rejection of claim 1].

3. Claims 7 and 8 are rejected under 35 U.S.C. § 103(a) as being unpatentable over Applicant's Admitted Prior Art (**APA**) in view of **Goodman**, Danny, "Danny Goodman's JavaScript Handbook" IDG Books Worldwide, 1996, pages 32-35, and further in view of well known prior art.

As per dependent claims 7 & 8:

APA, as modified by **Goodman**, discloses the invention substantially as claimed, as discussed above in the rejections of claims 1-6.

However, **APA & Goodman** do not *explicitly* teach the use of the and <embed> HTML elements.

"Official Notice" is taken that the selection of a particular HTML element or "tag" (such as or <embed>) is a design choice well known to those of ordinary skill in the art, and such choice is ordinarily motivated so as to accommodate the particular requirements of an end user, such as using the tag to embed an image in a web page, or using the <embed> tag to add sound to a web page. Accordingly, the claimed arrangement does not constitute a limitation that is patentably distinct from well known practices in the art [MPEP 2144.03].

4. Prior Art not relied upon:

Please refer to the references listed on the attached PTO-892 which are not relied upon in the claim rejections detailed above.

Application/Control Number:
09/916,253
Art Unit: 2126

Page 6

How to Contact the Examiner:

Any inquiry concerning this communication or earlier communications from the Examiner should be directed to **St. John Courtenay III** whose voice telephone number is **(703) 308-5217**. A voice mail service is also available at this number. Normal Flex work schedule: M – F 7:30 AM - 4:00 PM

- **All responses sent by U.S. Mail should be mailed to:**

Commissioner for Patents
PO Box 1450
Alexandria, VA 22313-1450

Patent Customers advised to FAX communications to the USPTO

<http://www.uspto.gov/web/offices/pac/dapp/opla/preognotice/faxnotice.pdf>

Effective Oct. 15, 2003, ALL patent application correspondence transmitted by FAX must be directed to the new PTO central FAX number:


**NEW PTO CENTRAL FAX NUMBER:
703-872-9306**

-
- Any inquiry of a general nature or relating to the status of this application should be directed to the **TC 2100 Group receptionist: (703) 305-3900.**

Please direct inquiries regarding fees, paper matching, and other issues not involving the Examiner to:

Technical Center 2100 CUSTOMER SERVICE: 703 306-5631

The Manual of Patent Examining Procedure (MPEP) is available online at:
<http://www.uspto.gov/web/offices/pac/mpep/index.html>


**ST. JOHN COURTENAY III
PRIMARY EXAMINER**

**NOTICE OF OFFICE PLAN TO CEASE SUPPLYING COPIES OF CITED U.S. PATENT
REFERENCES WITH OFFICE ACTIONS, AND PILOT TO EVALUATE THE
ALTERNATIVE OF PROVIDING ELECTRONIC ACCESS TO SUCH U.S. PATENT
REFERENCES**

Summary

The United States Patent and Trademark Office (Office or USPTO) plans in the near future to: (1) cease mailing copies of U.S. patents and U.S. patent application publications (US patent references) with Office actions except for citations made during the international stage of an international application under the Patent Cooperation Treaty and those made during reexamination proceedings; and (2) provide electronic access to, with convenient downloading capability of, the US patent references cited in an Office action via the Office's private Patent Application Information Retrieval (PAIR) system which has a new feature called "E-Patent Reference." Before ceasing to provide copies of U.S. patent references with Office actions, the Office shall test the feasibility of the E-Patent Reference feature by conducting a two-month pilot project starting with Office actions mailed after December 1, 2003. The Office shall evaluate the pilot project and publish the results in a notice which will be posted on the Office's web site (www.USPTO.gov) and in the Patent Official Gazette (O.G.). In order to use the new E-Patent Reference feature during the pilot period, or when the Office ceases to send copies of U.S. patent references with Office actions, the applicant must: (1) obtain a digital certificate from the Office; (2) obtain a customer number from the Office, and (3) properly associate applications with the customer number. The pilot project does not involve or affect the current Office practice of supplying paper copies of foreign patent documents and non-patent literature with Office actions. Paper copies of references will continue to be provided by the USPTO for searches and written opinions prepared by the USPTO for international applications during the international stage and for reexamination proceedings.

Description of Pilot Project to Provide Electronic Access to Cited U.S. Patent References

On December 1, 2003, the Office will make available a new feature, E-Patent Reference, in the Office's private PAIR system, to allow more convenient downloading of U.S. patents and U.S. patent application publications. The new feature will allow an authorized user of private PAIR to download some or all of the U.S. patents and U.S. patent application publications cited by an examiner on form PTO-892 in Office actions, as well as U.S. patents and U.S. patent application publications submitted by applicants on form PTO/SB08 (1449) as part of an IDS. The retrieval of some or all of the documents may be performed in one downloading step with the documents encoded as Adobe Portable Document format (.pdf) files, which is an improvement over the current page-by-page retrieval capability from other USPTO systems.

Steps to Use the New E-Patent Reference Feature During the Pilot Project and Thereafter

Access to private PAIR is required to utilize E-Patent Reference. If you don't already have access to private PAIR, the Office urges practitioners, and applicants not represented by a practitioner, to take advantage of the transition period to obtain a no-cost USPTO Public Key Infrastructure (PKI) digital certificate, obtain a USPTO customer number, associate all of their pending and new application filings with their customer number, install no-cost software (supplied by the Office) required to access private PAIR and E-Patent Reference feature, and make appropriate arrangements for Internet access. The full instructions for obtaining a PKI digital certificate are available at the Office's Electronic Business Center (EBC) web page at: <http://www.uspto.gov/ebc/downloads.html>. Note that a notarized signature will be required to obtain a digital certificate.

To get a Customer Number, download and complete the Customer Number Request form, PTO-SB125, at: <http://www.uspto.gov/web/forms/sb0125.pdf>. The completed form can then be transmitted by facsimile to the Electronic Business Center at (703) 308-2840, or mailed to the address on the form. If you are a registered attorney or patent agent, then your registration number must be associated with your customer number. This is accomplished by adding your registration number to the Customer Number Request form. A description of associating a customer number with an application is described at the EBC web page at: http://www.uspto.gov/ebc/registration_pair.html.

The E-Patent Reference feature will be accessed using a new button on the private PAIR screen. Ordinarily all of the cited U.S. patent and U.S. patent application publication references will be available over the Internet using the Office's new E-Patent Reference feature. The size of the references to be downloaded will be displayed by E-Patent Reference so the download time can be estimated. Applicants and registered practitioners can select to download all of the references or any combination of cited references. Selected references will be downloaded as complete documents as Adobe Portable Document Format (.pdf) files. For a limited period of time, the USPTO will include a copy of this notice with Office actions to encourage applicants to use this new feature and, if needed, to take the steps outlined above in order to be able to utilize this new feature during the pilot and thereafter.

During the two-month pilot, the Office will evaluate the stability and capacity of the E-Patent Reference feature to reliably provide electronic access to cited U.S. patent and U.S. patent application publication references. While copies of U.S. patent and U.S. patent application publication references cited by examiners will continue to be mailed with Office actions during the pilot project, applicants are encouraged to use the private PAIR and the E-Patent Reference feature to electronically access and download cited U.S. patent and U.S. patent application publication references so the Office will be able to objectively evaluate its performance. The public is encouraged to submit comments to the Office on the usability and performance of the E-Patent Reference feature during the pilot. Further, during the pilot period registered practitioners, and applicants not represented by a practitioner, are encouraged to experiment with the feature, develop a proficiency in using the feature, and establish new internal processes for using the new access to the cited U.S. patents and U.S. patent application publications to prepare for the anticipated cessation of the current Office practice of supplying copies of such cited

references. The Office plans to continue to provide access to the E-Patent Reference feature during its evaluation of the pilot.

Comments

Comments concerning the E-Patent Reference feature should be in writing and directed to the Electronic Business Center (EBC) at the USPTO by electronic mail at eReference@uspto.gov or by facsimile to (703) 308-2840. Comments will be posted and made available for public inspection. To ensure that comments are considered in the evaluation of the pilot project, comments should be submitted in writing by January 15, 2004.

Comments with respect to specific applications should be sent to the Technology Centers' customer service centers. Comments concerning digital certificates, customer numbers, and associating customer numbers with applications should be sent to the Electronic Business Center (EBC) at the USPTO by facsimile at (703) 308-2840 or by e-mail at EBC@uspto.gov.

Implementation after Pilot

After the pilot, its evaluation, and publication of a subsequent notice as indicated above, the Office expects to implement its plan to cease mailing paper copies of U.S. patent references cited during examination of non provisional applications on or after February 2, 2004; although copies of cited foreign patent documents, as well as non-patent literature, will still be mailed to the applicant until such time as substantially all applications have been scanned into IFW.

For Further Information Contact

Technical information on the operation of the IFW system can be found on the USPTO website at <http://www.uspto.gov/web/patents/ifw/index.html>. Comments concerning the E-Patent Reference feature and questions concerning the operation of the PAIR system should be directed to the EBC at the USPTO at (866) 217-9197. The EBC may also be contacted by facsimile at (703) 308-2840 or by e-mail at EBC@uspto.gov.

Date. 12/1/03



Nicholas P. Godici
Commissioner for Patents

USPTO TO PROVIDE ELECTRONIC ACCESS TO CITED U.S. PATENT REFERENCES WITH OFFICE ACTIONS AND CEASE SUPPLYING PAPER COPIES

In support of its 21st Century Strategic Plan goal of increased patent e-Government, beginning in June 2004, the United States Patent and Trademark Office (Office or USPTO) will begin the phase-in of its E-Patent Reference program and hence will: (1) **provide downloading capability of the U.S. patents and U.S. patent application publications cited in Office actions** via the E-Patent Reference feature of the Office's Patent Application Information Retrieval (PAIR) system; and (2) **cease mailing paper copies of U.S. patents and U.S. patent application publications with Office actions** (in applications and during reexamination proceedings) except for citations made during the international stage of an international application under the Patent Cooperation Treaty (PCT). In order to use the new E-Patent Reference feature applicants must: (1) obtain a digital certificate and software from the Office; (2) obtain a customer number from the Office; and (3) properly associate patent applications with the customer number. Alternatively, copies of all U.S. patents and patent application publications can be accessed without a digital certificate from the USPTO web site, from the USPTO Office of Public Records, and from commercial sources. The Office will continue the practice of supplying paper copies of foreign patent documents and non-patent literature with Office actions. Paper copies of cited references will continue to be provided by the USPTO for international applications during the international stage.

Schedule

June 2004	TCs 1600, 1700, 2800 and 2900
July 2004	TCs 3600 and 3700
August 2004	TCs 2100 and 2600

All U.S. patents and U.S. patent application publications are available on the USPTO web site. However, a simple system for downloading the cited U.S. patents and patent application publications has been established for applicants, called the E-Patent Reference system. As E-Patent Reference and Private PAIR require participating applicants to have a customer number, retrieval software and a digital certificate, all applicants are strongly encouraged to contact the Patent Electronic Business Center to acquire these items. To be ready to use this system by June 1, 2004, contact the Patent EBC as soon as possible by phone at 866-217-9197 (toll-free), 703-305-3028 or 703-308-6845 or electronically via the Internet at ebc@uspto.gov.

Other Options

The E-Patent Reference function requires the applicant to use the secure Private PAIR system, which establishes confidential communications with the applicant. Applicants using this facility must receive a digital certificate, as described above. Other options for obtaining patents which do not require the digital certificate include the USPTO's free Patents on the Web program (<http://www.uspto.gov/patft/index.html>). The USPTO's Office of Public Records also supplies copies of patents for a fee (<http://ebiz1.uspto.gov/oems25p/index.html>). Commercial sources also provide U.S. patents and patent application publications.

For complete instructions see the Official Gazette Notice, USPTO TO PROVIDE ELECTRONIC ACCESS TO CITED U.S. PATENT REFERENCES WITH OFFICE ACTIONS AND CEASE SUPPLYING PAPER COPIES, on the USPTO web site.

Notice of References Cited	Application/Control No. 09/916,253	Applicant(s)/Patent Under Reexamination GAO ET AL.	
	Examiner St. John Courtenay III	Art Unit 2126	Page 1 of 1

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
	A	US-6,480,860 B1	11-2002	Monday, Paul Brian	707/102
	B	US-6,546,419 B1	04-2003	Humpleman et al.	709/223
	C	US-			
	D	US-			
	E	US-			
	F	US-			
	G	US-			
	H	US-			
	I	US-			
	J	US-			
	K	US-			
	L	US-			
	M	US-			

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	Goodman, Danny, "Danny Goodman's JavaScript Handbook" IDG Books Worldwide, 1996, pages 32-35
	V	Box et al., "Simple Object Access Protocol (SOAP) 1.1", W3C Note 08, May 2000, pages 1-31, www.w3.org/TR/2000/NOTE-SOAP-20000508/
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

GOODMAN

Danny Goodman's JavaScript® Handbook

Danny Goodman



IDG Books Worldwide, Inc.

Foster City, CA • Chicago, IL • Indianapolis, IN • Braintree, MA • Southlake, TX

Danny Goodman's JavaScript® Handbook

Published by
IDG Books Worldwide, Inc.
An International Data Group Company
919 E. Hillsdale Blvd.
Suite 400
Foster City, CA 94404

Text, art, and software compilations copyright © 1996 by IDG Books Worldwide, Inc. All rights reserved. No part of this book, including interior design, cover design, and icons, may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording, or otherwise) without the prior written permission of the publisher.

Library of Congress Catalog Card No.: 96-75747

ISBN: 0-7645-3003-8

Printed in the United States of America

10 9 8 7 6 5 4 3 2 1

1E/SS/QU/ZW/IN

Distributed in the United States by IDG Books Worldwide, Inc.

Distributed by Macmillan Canada for Canada; by Computer and Technical Books for the Caribbean Basin; by Contemporanea de Ediciones for Venezuela; by Distribuidora Cuspidor for Argentina; by CITEC for Brazil; by Ediciones ZETA S.C.R. Ltda. for Peru; by Editorial Limusa SA for Mexico; by Transworld Publishers Limited in the United Kingdom and Europe; by Al-Maiman Publishers & Distributors for Saudi Arabia; by Simron Pty. Ltd. for South Africa; by IDG Communications (HK) Ltd. for Hong Kong; by Toppan Company Ltd. for Japan; by Addison Wesley Publishing Company for Korea; by Longman Singapore Publishers Ltd. for Singapore, Malaysia, Thailand, and Indonesia; by Unalis Corporation for Taiwan; by WS Computer Publishing Company, Inc. for the Philippines; by Woodslane Pty. Ltd. for Australia; by Woodslane Enterprises Ltd. for New Zealand.

For information on IDG Books Worldwide's books in the U.S., please call our Consumer Customer Service department at 800-762-2974. For reseller information, including discounts and premium sales, please call our Reseller Customer Service department at 800-434-3422.

For information on where to purchase IDG Books Worldwide's books outside the U.S., contact IDG Books Worldwide at 415-655-3021 or fax 415-655-3295.

For information on translations, contact Marc Jeffrey Mikulich, Director, Foreign & Subsidiary Rights, at IDG Books Worldwide, 415-655-3018 or fax 415-655-3295.

For sales inquiries and special prices for bulk quantities, write to the address above or call IDG Books Worldwide at 415-655-3200.

For information on using IDG Books Worldwide's books in the classroom, or ordering examination copies, contact the Education Office at 800-434-2086 or fax 817-251-8174.

For authorization to photocopy items for corporate, personal, or educational use, please contact Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, or fax 508-750-4470.

Limit of Liability/Disclaimer of Warranty: Author and Publisher have used their best efforts in preparing this book. IDG Books Worldwide, Inc., and Author make no representation or warranties with respect to the accuracy or completeness of the contents of this book and specifically disclaim any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages.

Trademarks: All brand names and product names used in this book are trademarks, registered trademarks, or trade names of their respective holders. IDG Books Worldwide is not associated with any product or vendor mentioned in this book.



is a trademark under exclusive
license to IDG Books Worldwide, Inc.,
from International Data Group, Inc.

3. Save the document with the name script1.htm.

(This is the lowest common denominator file-naming convention for Windows 3.1 — feel free to use a .html extension if your operating system allows it.)

4. Switch to your browser.
5. Choose Open File from the File menu, and select script1.htm.

If you typed all lines as directed, the document in the browser window should look like the one in Figure 3-3. If the browser indicates that there is a mistake somewhere, don't do anything for now. Let's first examine the details of the entire document so you understand some of the finer points of what the script is doing.

Examining the Script

It's not important for you to memorize any of the commands or syntax we'll be discussing in this section. Instead, relax and watch how the lines of the script become what you see in the browser.

All lines up to the `<SCRIPT>` tag are very standard HTML. Your JavaScript-enhanced HTML documents should contain the same style of opening tags you normally use.

The `<SCRIPT>` tag

Anytime you include JavaScript verbiage in an HTML document, you must enclose those lines inside a `<SCRIPT>...</SCRIPT>` tag pair. These tags alert the browser program to begin interpreting all the text between these tags as a script. Because other scripting languages may arrive in the future, you must specify the precise name of the language in which the enclosed code is written. Therefore, when the browser receives this signal that our script uses the JavaScript language, it uses its built-in JavaScript interpreter to handle the code. There are parallels to this in real life: If you have a French interpreter at your side, you need to know that the person with whom you are conversing also knows French. If you encounter someone from Russia, the French interpreter won't be able to help you. Similarly, if your browser has only a JavaScript interpreter inside, it won't be able to understand code written in VBScript.

Now is a good time to instill an aspect of JavaScript that will be important to you throughout all your scripting ventures: JavaScript is case-sensitive. Therefore, any item in your scripts that uses a JavaScript word, such as the name of the JavaScript language in the `<SCRIPT>` tag, must be entered with the correct upper- and lowercase letters.

Your HTML tags (including the `<SCRIPT>` tag) can be in your choice of upper- or lowercase, but everything in JavaScript is case-sensitive. When a line of JavaScript doesn't work, that's the first thing to look for. Always compare your typed code against the listings printed in this book and against the various vocabulary entries discussed throughout.

A script for all browsers

The next line after the `<SCRIPT>` tag appears to be the beginning of an HTML comment tag. It is, but the JavaScript interpreter treats comment tags in a special way. Although JavaScript dutifully ignores a line that begins with an HTML comment start tag, it treats the next line as a full-fledged script line. In other words, the browser begins interpreting the next line after a comment start tag. If you want to put a comment inside JavaScript code, the comment must start with a double slash (`//`). Such a comment may go at the end of a line (such as after a JavaScript statement that is to be interpreted by the browser) or on its own line. In fact, the latter case appears near the end of the script. The comment line starts with two slashes.

Step back for a moment and notice that the entire script (including comments) is contained inside a standard HTML comment tag (`<!--comment-->`). The value of this containment is not clear until you see what happens to your scripted HTML document in a non-JavaScript-compatible browser. Such a browser would blow past the `<SCRIPT>` tag as being an advanced tag it doesn't understand. Although the browser would respect the regular comment start tag (`<!--`), it would treat the one line of script as regular body text. Figure 3-4 shows the results of our first script when viewed in a pre-Java version of Microsoft's Internet Explorer. Remember that many users don't have access to modern browsers or graphical browsers (they use the Lynx text-oriented UNIX Web reader software). By embracing your script lines within these comments, your Web pages won't look completely broken in relatively modern non-JavaScript browsers.

Notice, too, that the comment lines that shield older browsers from your scripts go inside the `<SCRIPT>...</SCRIPT>` tags. Do not put these comment lines above the `<SCRIPT>` tag or below the `</SCRIPT>` tag and expect them to work.

One more issue about the script-hiding comment lines in this book. To save space on the page, most examples do not have comment lines inserted in them. But as you will see in later chapters where full-fledged examples are provided, the comment lines are where they should be. For any pages you produce for public consumption, always encase your script lines inside these comments.

Displaying some text

The script line utilizes one of the possible actions a script can ask a document to perform (`document.write()`, meaning display text in the current document). You'll learn more about the document object in Chapter 8.




Figure 3-4: Failing to contain script lines in comments causes those lines to be treated as body text in an old browser.

Whenever we ask an object (a document in this case) to perform a task for us, the name of the task is always followed by a set of parentheses. In some cases — the `write()` task, for example — JavaScript needs to know what information it should act on. That information (called a *parameter*) goes inside parentheses after the name of the task. Thus, if we wanted to write the name of the first U.S. President to a document, the commands would be

```
document.write("George Washington")
```

The line of text that our script writes includes some static text ("Last updated on"), some evaluated text (the date and time at which the current HTML document was last modified), and one more character of static text for the sentence's period ("."). JavaScript uses the plus symbol (+) to join (*concatenate*) text components into a larger, single string of text characters. Neither JavaScript nor the + symbol knows anything about words and spaces, so it is up to the script to make sure that the proper spaces

are passed along as part of the parameter. Notice, therefore, that there is an extra space after the word "updated" in the first part of the `document.write()` parameter.

To fetch the last modified date of the document for our parameter, we call upon JavaScript to extract one of the document's properties. We extract a property by appending the property name to the object name (document in this case), and separate the two names with a period. If you are searching for some English to assign to this scheme in your head as you read it, start from the right side and call the right side item a property "of" the left side: the `lastModified` property of the document object. This dot syntax looks a lot like the `document.write()` task, but a property name does not have parentheses after it. In any case, the reference to the property in the script tells JavaScript to insert the value of that property in the spot where the call is made. For your first attempt at the script, JavaScript substitutes the last modified date recorded by your computer for that call as part of the text string that gets written to the document.

Have Some Fun

If you encountered an error in your first attempt at loading this document into your browser, go back to the text editor and check the lines of the script section against Listing 3-1, looking carefully at each line in light of our explanations. There may be a single character out of place, a lowercase letter where an uppercase one belongs, or a quote or parenthesis missing. Make the necessary repairs, switch to your browser, and click the Reload button.

To see how dynamic the script is, go back into the text editor and replace the word "updated" with "changed." Save, switch, and reload to see how the script has changed the text in the document and that the time is more recent than your first attempt. Feel free to substitute other text for the quoted text in the `document.write()` statement. Or add more text with additional `document.write()` statements. The parameters to `document.write()` are HTML text, so you can even write a "
" to make a line break. Always be sure to save, switch, and reload to see the results of your handiwork.

On We Go

From here we dive into the JavaScript language, beginning with an aerial view of the landscape prior to targeting specific features. Much of what you've experienced in this chapter and in your first script will be explained in greater detail in the chapters ahead.

Box et.al.

Simple Object Access Protocol (SOAP) 1.1

W3C Note 08 May 2000

This version:

<http://www.w3.org/TR/2000/NOTE-SOAP-20000508>

Latest version:

<http://www.w3.org/TR/SOAP>

Authors (alphabetically):

Don Box, DevelopMentor

David Ehnebuske, IBM

Gopal Kakivaya, Microsoft

Andrew Layman, Microsoft

Noah Mendelsohn, Lotus Development Corp.

Henrik Frystyk Nielsen, Microsoft

Satish Thatte, Microsoft

Dave Winer, UserLand Software, Inc.

Copyright© 2000 DevelopMentor, International Business Machines Corporation, Lotus Development Corporation, Microsoft, UserLand Software

Abstract

SOAP is a lightweight protocol for exchange of information in a decentralized, distributed environment. It is an XML based protocol that consists of three parts: an envelope that defines a framework for describing what is in a message and how to process it, a set of encoding rules for expressing instances of application-defined datatypes, and a convention for representing remote procedure calls and responses. SOAP can potentially be used in combination with a variety of other protocols; however, the only bindings defined in this document describe how to use SOAP in combination with HTTP and HTTP Extension Framework.

Status

This document is a submission to the World Wide Web Consortium (see Submission Request, W3C Staff Comment) to propose the formation of a working group in the area of XML-based protocols. Comments are welcome to the authors but you are encouraged to share your views on the W3C's public mailing list [<xml-dist-app@w3.org>](mailto:xml-dist-app@w3.org) (see archives).

This document is a NOTE made available by the W3C for discussion only. Publication of this Note by W3C indicates no endorsement by W3C or the W3C Team, or any W3C Members. W3C has had no editorial control over the preparation of this Note. This document is a work in progress and may be updated, replaced, or rendered obsolete by other documents at any time.

A list of current W3C technical documents can be found at the Technical Reports page.

Table of Contents

- 1. Introduction
 - 1.1 Design Goals
 - 1.2 Notational Conventions
 - 1.3 Examples of SOAP Messages
- 2. The SOAP Message Exchange Model
- 3. Relation to XML
- 4. SOAP Envelope
 - 4.1.1 SOAP encodingStyle Attribute
 - 4.1.2 Envelope Versioning Model
 - 4.2 SOAP Header
 - 4.2.1 Use of Header Attributes
 - 4.2.2 SOAP actor Attribute
 - 4.2.3 SOAP mustUnderstand Attribute
 - 4.3 SOAP Body
 - 4.3.1 Relationship between SOAP Header and Body
 - 4.4 SOAP Fault
 - 4.4.1 SOAP Fault Codes
- 5. SOAP Encoding
 - 5.1 Rules for Encoding Types in XML
 - 5.2 Simple Types
 - 5.2.1 Strings
 - 5.2.2 Enumerations
 - 5.2.3 Array of Bytes
 - 5.3 Polymorphic Accessor
 - 5.4 Compound Types
 - 5.4.1 Compound Values and References to Values
 - 5.4.2 Arrays
 - 5.4.2.1 PartiallyTransmitted Arrays
 - 5.4.2.2 SparseArrays
 - 5.4.3 Generic Compound Types
 - 5.5 Default Values
 - 5.6 SOAP root Attribute
- 6. Using SOAP in HTTP
 - 6.1 SOAP HTTP Request
 - 6.1.1 The SOAPAction HTTP Header Field
 - 6.2 SOAP HTTP Response
 - 6.3 The HTTP Extension Framework
 - 6.4 SOAP HTTP Examples
- 7. Using SOAP for RPC
 - 7.1 RPC and SOAP Body
 - 7.2 RPC and SOAP Header
- 8. Security Considerations
- 9. References
 - A. SOAP Envelope Examples
 - A.1 Sample Encoding of Call Requests
 - A.2 Sample Encoding of Response

1. Introduction

SOAP provides a simple and lightweight mechanism for exchanging structured and typed information between peers in

a decentralized, distributed environment using XML. SOAP does not itself define any application semantics such as a programming model or implementation specific semantics; rather it defines a simple mechanism for expressing application semantics by providing a modular packaging model and encoding mechanisms for encoding data within modules. This allows SOAP to be used in a large variety of systems ranging from messaging systems to RPC.

SOAP consists of three parts:

- The SOAP envelope (see [section 4](#)) construct defines an overall framework for expressing **what** is in a message; **who** should deal with it, and **whether** it is optional or mandatory.
- The SOAP encoding rules (see [section 5](#)) defines a serialization mechanism that can be used to exchange instances of application-defined datatypes.
- The SOAP RPC representation (see [section 7](#)) defines a convention that can be used to represent remote procedure calls and responses.

Although these parts are described together as part of SOAP, they are functionally orthogonal. In particular, the envelope and the encoding rules are defined in different namespaces in order to promote simplicity through modularity.

In addition to the SOAP envelope, the SOAP encoding rules and the SOAP RPC conventions, this specification defines two protocol bindings that describe how a SOAP message can be carried in HTTP [\[5\]](#) messages either with or without the HTTP Extension Framework [\[6\]](#).

1.1 Design Goals

A major design goal for SOAP is simplicity and extensibility. This means that there are several features from traditional messaging systems and distributed object systems that are not part of the core SOAP specification. Such features include

- Distributed garbage collection
- Boxcarring or batching of messages
- Objects-by-reference (which requires distributed garbage collection)
- Activation (which requires objects-by-reference)

1.2 Notational Conventions

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC-2119 [\[2\]](#).

The namespace prefixes "SOAP-ENV" and "SOAP-ENC" used in this document are associated with the SOAP namespaces "<http://schemas.xmlsoap.org/soap/envelope/>" and "<http://schemas.xmlsoap.org/soap/encoding/>" respectively.

Throughout this document, the namespace prefix "xsi" is assumed to be associated with the URI "<http://www.w3.org/1999/XMLSchema-instance>" which is defined in the XML Schemas specification [\[11\]](#). Similarly, the namespace prefix "xsd" is assumed to be associated with the URI "<http://www.w3.org/1999/XMLSchema>" which is defined in [\[10\]](#). The namespace prefix "tns" is used to indicate whatever is the target namespace of the current document. All other namespace prefixes are samples only.

Namespace URIs of the general form "some-URI" represent some application-dependent or context-dependent URI [\[4\]](#).

This specification uses the augmented Backus-Naur Form (BNF) as described in RFC-2616 [5] for certain constructs.

1.3 Examples of SOAP Messages

In this example, a GetLastTradePrice SOAP request is sent to a StockQuote service. The request takes a string parameter, ticker symbol, and returns a float in the SOAP response. The SOAP Envelope element is the top element of the XML document representing the SOAP message. XML namespaces are used to disambiguate SOAP identifiers from application specific identifiers. The example illustrates the HTTP bindings defined in [section 6](#). It is worth noting that the rules governing XML payload format in SOAP are entirely independent of the fact that the payload is carried in HTTP.

More examples are available in [Appendix A](#).

Example 1 SOAP Message Embedded in HTTP Request

```
POST /StockQuote HTTP/1.1
Host: www.stockquoteserver.com
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
SOAPAction: "Some-URI"

<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <m:GetLastTradePrice xmlns:m="Some-URI">
      <symbol>DIS</symbol>
    </m:GetLastTradePrice>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Following is the response message containing the HTTP message with the SOAP message as the payload:

Example 2 SOAP Message Embedded in HTTP Response

```
HTTP/1.1 200 OK
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn

<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <m:GetLastTradePriceResponse xmlns:m="Some-URI">
      <Price>34.5</Price>
    </m:GetLastTradePriceResponse>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2. The SOAP Message Exchange Model

SOAP messages are fundamentally one-way transmissions from a sender to a receiver, but as illustrated above, SOAP messages are often combined to implement patterns such as request/response.

SOAP implementations can be optimized to exploit the unique characteristics of particular network systems. For example, the HTTP binding described in [section 6](#) provides for SOAP response messages to be delivered as HTTP responses, using the same connection as the inbound request.

Regardless of the protocol to which SOAP is bound, messages are routed along a so-called "message path", which allows for processing at one or more intermediate nodes in addition to the ultimate destination.

A SOAP application receiving a SOAP message **MUST** process that message by performing the following actions in the order listed below:

1. Identify all parts of the SOAP message intended for that application (see [section 4.2.2](#))
2. Verify that all mandatory parts identified in [step 1](#) are supported by the application for this message (see [section 4.2.3](#)) and process them accordingly. If this is not the case then discard the message (see [section 4.4](#)). The processor **MAY** ignore optional parts identified in [step 1](#) without affecting the outcome of the processing.
3. If the SOAP application is not the ultimate destination of the message then remove all parts identified in [step 1](#) before forwarding the message.

Processing a message or a part of a message requires that the SOAP processor understands, among other things, the exchange pattern being used (one way, request/response, multicast, etc.), the role of the recipient in that pattern, the employment (if any) of RPC mechanisms such as the one documented in [section 7](#), the representation or encoding of data, as well as other semantics necessary for correct processing.

While attributes such as the SOAP `encodingStyle` attribute (see [section 4.1.1](#)) can be used to describe certain aspects of a message, this specification does not mandate a particular means by which the recipient makes such determinations in general. For example, certain applications will understand that a particular `<getStockPrice>` element signals an RPC request using the conventions of [section 7](#), while another application may infer that all traffic directed to it is encoded as one way messages.

3. Relation to XML

All SOAP messages are encoded using XML (see [\[7\]](#) for more information on XML).

A SOAP application **SHOULD** include the proper SOAP namespace on all elements and attributes defined by SOAP in messages that it generates. A SOAP application **MUST** be able to process SOAP namespaces in messages that it receives. It **MUST** discard messages that have incorrect namespaces (see [section 4.4](#)) and it **MAY** process SOAP messages without SOAP namespaces as though they had the correct SOAP namespaces.

SOAP defines two namespaces (see [\[8\]](#) for more information on XML namespaces):

- The SOAP envelope has the namespace identifier "<http://schemas.xmlsoap.org/soap/envelope/>"
- The SOAP serialization has the namespace identifier "<http://schemas.xmlsoap.org/soap/encoding/>"

A SOAP message **MUST NOT** contain a Document Type Declaration. A SOAP message **MUST NOT** contain Processing Instructions. [\[7\]](#)

SOAP uses the local, unqualified "id" attribute of type "ID" to specify the unique identifier of an encoded element. SOAP uses the local, unqualified attribute "href" of type "uri-reference" to specify a reference to that value, in a

manner conforming to the XML Specification [7], XML Schema Specification [11], and XML Linking Language Specification [9].

With the exception of the SOAP mustUnderstand attribute (see [section 4.2.3](#)) and the SOAP actor attribute (see [section 4.2.2](#)), it is generally permissible to have attributes and their values appear in XML instances or alternatively in schemas, with equal effect. That is, declaration in a DTD or schema with a default or fixed value is semantically equivalent to appearance in an instance.

4. SOAP Envelope

A SOAP message is an XML document that consists of a mandatory SOAP envelope, an optional SOAP header, and a mandatory SOAP body. This XML document is referred to as a SOAP message for the rest of this specification. The namespace identifier for the elements and attributes defined in this section is

["http://schemas.xmlsoap.org/soap/envelope/"](http://schemas.xmlsoap.org/soap/envelope/). A SOAP message contains the following:

- The Envelope is the top element of the XML document representing the message.
- The Header is a generic mechanism for adding features to a SOAP message in a decentralized manner without prior agreement between the communicating parties. SOAP defines a few attributes that can be used to indicate who should deal with a feature and whether it is optional or mandatory (see [section 4.2](#))
- The Body is a container for mandatory information intended for the ultimate recipient of the message (see [section 4.3](#)). SOAP defines one element for the body, which is the Fault element used for reporting errors.

The grammar rules are as follows:

1. Envelope

- The element name is "Envelope".
- The element MUST be present in a SOAP message
- The element MAY contain namespace declarations as well as additional attributes. If present, such additional attributes MUST be namespace-qualified. Similarly, the element MAY contain additional sub elements. If present these elements MUST be namespace-qualified and MUST follow the SOAP Body element.

2. Header (see [section 4.2](#))

- The element name is "Header".
- The element MAY be present in a SOAP message. If present, the element MUST be the first immediate child element of a SOAP Envelope element.
- The element MAY contain a set of header entries each being an immediate child element of the SOAP Header element. All immediate child elements of the SOAP Header element MUST be namespace-qualified.

3. Body (see [section 4.3](#))

- The element name is "Body".
- The element MUST be present in a SOAP message and MUST be an immediate child element of a SOAP Envelope element. It MUST directly follow the SOAP Header element if present. Otherwise it MUST be the first immediate child element of the SOAP Envelope element.
- The element MAY contain a set of body entries each being an immediate child element of the SOAP Body element. Immediate child elements of the SOAP Body element MAY be namespace-qualified. SOAP defines the SOAP Fault element, which is used to indicate error messages (see [section 4.4](#)).

4.1.1 SOAP encodingStyle Attribute

The SOAP encodingStyle global attribute can be used to indicate the serialization rules used in a SOAP message. This attribute MAY appear on any element, and is scoped to that element's contents and all child elements not themselves containing such an attribute, much as an XML namespace declaration is scoped. There is no default encoding defined for a SOAP message.

The attribute value is an ordered list of one or more URIs identifying the serialization rule or rules that can be used to deserialize the SOAP message indicated in the order of most specific to least specific. Examples of values are

```
"http://schemas.xmlsoap.org/soap/encoding/"  
"http://my.host/encoding/restricted http://my.host/encoding/"  
"
```

The serialization rules defined by SOAP in section 5 are identified by the URI "<http://schemas.xmlsoap.org/soap/encoding/>". Messages using this particular serialization SHOULD indicate this using the SOAP encodingStyle attribute. In addition, all URIs syntactically beginning with "<http://schemas.xmlsoap.org/soap/encoding/>" indicate conformance with the SOAP encoding rules defined in [section 5](#) (though with potentially tighter rules added).

A value of the zero-length URI ("") explicitly indicates that no claims are made for the encoding style of contained elements. This can be used to turn off any claims from containing elements.

4.1.2 Envelope Versioning Model

SOAP does not define a traditional versioning model based on major and minor version numbers. A SOAP message MUST have an Envelope element associated with the "<http://schemas.xmlsoap.org/soap/envelope/>" namespace. If a message is received by a SOAP application in which the SOAP Envelope element is associated with a different namespace, the application MUST treat this as a version error and discard the message. If the message is received through a request/response protocol such as HTTP, the application MUST respond with a SOAP VersionMismatch faultcode message (see [section 4.4](#)) using the SOAP "<http://schemas.xmlsoap.org/soap/envelope/>" namespace.

4.2 SOAP Header

SOAP provides a flexible mechanism for extending a message in a decentralized and modular way without prior knowledge between the communicating parties. Typical examples of extensions that can be implemented as header entries are authentication, transaction management, payment etc.

The Header element is encoded as the first immediate child element of the SOAP Envelope XML element. All immediate child elements of the Header element are called header entries.

The encoding rules for header entries are as follows:

1. A header entry is identified by its fully qualified element name, which consists of the namespace URI and the local name. All immediate child elements of the SOAP Header element MUST be namespace-qualified.
2. The SOAP encodingStyle attribute MAY be used to indicate the encoding style used for the header entries (see [section 4.1.1](#)).
3. The SOAP mustUnderstand attribute (see [section 4.2.3](#)) and SOAP actor attribute (see [section 4.2.2](#)) MAY be used to indicate how to process the entry and by whom (see [section 4.2.1](#)).

4.2.1 Use of Header Attributes

The SOAP Header attributes defined in this section determine how a recipient of a SOAP message should process the message as described in [section 2](#). A SOAP application generating a SOAP message SHOULD only use the SOAP Header attributes on immediate child elements of the SOAP Header element. The recipient of a SOAP message MUST ignore all SOAP Header attributes that are not applied to an immediate child element of the SOAP Header element.

An example is a header with an element identifier of "Transaction", a "mustUnderstand" value of "1", and a value of 5. This would be encoded as follows:

```
<SOAP-ENV:Header>
  <t:Transaction
    xmlns:t="some-URI" SOAP-ENV:mustUnderstand="1">
    5
  </t:Transaction>
</SOAP-ENV:Header>
```

4.2.2 SOAP actor Attribute

A SOAP message travels from the originator to the ultimate destination, potentially by passing through a set of SOAP intermediaries along the message path. A SOAP intermediary is an application that is capable of both receiving and forwarding SOAP messages. Both intermediaries as well as the ultimate destination are identified by a URI.

Not all parts of a SOAP message may be intended for the ultimate destination of the SOAP message but, instead, may be intended for one or more of the intermediaries on the message path. The role of a recipient of a header element is similar to that of accepting a contract in that it cannot be extended beyond the recipient. That is, a recipient receiving a header element MUST NOT forward that header element to the next application in the SOAP message path. The recipient MAY insert a similar header element but in that case, the contract is between that application and the recipient of that header element.

The SOAP actor global attribute can be used to indicate the recipient of a header element. The value of the SOAP actor attribute is a URI. The special URI "<http://schemas.xmlsoap.org/soap/actor/next>" indicates that the header element is intended for the very first SOAP application that processes the message. This is similar to the hop-by-hop scope model represented by the Connection header field in HTTP.

Omitting the SOAP actor attribute indicates that the recipient is the ultimate destination of the SOAP message.

This attribute MUST appear in the SOAP message instance in order to be effective (see [section 3](#) and [4.2.1](#)).

4.2.3 SOAP mustUnderstand Attribute

The SOAP mustUnderstand global attribute can be used to indicate whether a header entry is mandatory or optional for the recipient to process. The recipient of a header entry is defined by the SOAP actor attribute (see [section 4.2.2](#)). The value of the mustUnderstand attribute is either "1" or "0". The absence of the SOAP mustUnderstand attribute is semantically equivalent to its presence with the value "0".

If a header element is tagged with a SOAP mustUnderstand attribute with a value of "1", the recipient of that header entry either MUST obey the semantics (as conveyed by the fully qualified name of the element) and process correctly to those semantics, or MUST fail processing the message (see [section 4.4](#)).

The SOAP mustUnderstand attribute allows for robust evolution. Elements tagged with the SOAP mustUnderstand attribute with a value of "1" MUST be presumed to somehow modify the semantics of their parent or peer elements. Tagging elements in this manner assures that this change in semantics will not be silently (and, presumably, erroneously) ignored by those who may not fully understand it.

This attribute **MUST** appear in the instance in order to be effective (see section 3 and 4.2.1).

4.3 SOAP Body

The SOAP Body element provides a simple mechanism for exchanging mandatory information intended for the ultimate recipient of the message. Typical uses of the Body element include marshalling RPC calls and error reporting.

The Body element is encoded as an immediate child element of the SOAP Envelope XML element. If a Header element is present then the Body element **MUST** immediately follow the Header element, otherwise it **MUST** be the first immediate child element of the Envelope element.

All immediate child elements of the Body element are called body entries and each body entry is encoded as an independent element within the SOAP Body element.

The encoding rules for body entries are as follows:

1. A body entry is identified by its fully qualified element name, which consists of the namespace URI and the local name. Immediate child elements of the SOAP Body element **MAY** be namespace-qualified.
2. The SOAP encodingStyle attribute **MAY** be used to indicate the encoding style used for the body entries (see section 4.1.1).

SOAP defines one body entry, which is the Fault entry used for reporting errors (see section 4.4).

4.3.1 Relationship between SOAP Header and Body

While the Header and Body are defined as independent elements, they are in fact related. The relationship between a body entry and a header entry is as follows: A body entry is semantically equivalent to a header entry intended for the default actor and with a SOAP mustUnderstand attribute with a value of "1". The default actor is indicated by not using the actor attribute (see section 4.2.2).

4.4 SOAP Fault

The SOAP Fault element is used to carry error and/or status information within a SOAP message. If present, the SOAP Fault element **MUST** appear as a body entry and **MUST NOT** appear more than once within a Body element.

The SOAP Fault element defines the following four subelements:

faultcode

The faultcode element is intended for use by software to provide an algorithmic mechanism for identifying the fault. The faultcode **MUST** be present in a SOAP Fault element and the faultcode value **MUST** be a qualified name as defined in [8], section 3. SOAP defines a small set of SOAP fault codes covering basic SOAP faults (see section 4.4.1)

faultstring

The faultstring element is intended to provide a human readable explanation of the fault and is not intended for algorithmic processing. The faultstring element is similar to the 'Reason-Phrase' defined by HTTP (see [5], section 6.1). It **MUST** be present in a SOAP Fault element and **SHOULD** provide at least some information explaining the nature of the fault.

faultactor

The faultactor element is intended to provide information about who caused the fault to happen within the message path (see section 2). It is similar to the SOAP actor attribute (see section 4.2.2) but instead of indicating the destination of the header entry, it indicates the source of the fault. The value of the faultactor attribute is a

URI identifying the source. Applications that do not act as the ultimate destination of the SOAP message **MUST** include the faultactor element in a SOAP Fault element. The ultimate destination of a message **MAY** use the faultactor element to indicate explicitly that it generated the fault (see also the [detail element below](#)).

detail

The detail element is intended for carrying application specific error information related to the Body element. It **MUST** be present if the contents of the Body element could not be successfully processed. It **MUST NOT** be used to carry information about error information belonging to header entries. Detailed error information belonging to header entries **MUST** be carried within header entries.

The absence of the detail element in the Fault element indicates that the fault is not related to processing of the Body element. This can be used to distinguish whether the Body element was processed or not in case of a fault situation.

All immediate child elements of the detail element are called detail entries and each detail entry is encoded as an independent element within the detail element.

The encoding rules for detail entries are as follows (see also [example 10](#)):

1. A detail entry is identified by its fully qualified element name, which consists of the namespace URI and the local name. Immediate child elements of the detail element **MAY** be namespace-qualified.
2. The SOAP encodingStyle attribute **MAY** be used to indicate the encoding style used for the detail entries (see [section 4.1.1](#)).

Other Fault subelements **MAY** be present, provided they are namespace-qualified.

4.4.1 SOAP Fault Codes

The faultcode values defined in this section **MUST** be used in the faultcode element when describing faults defined by this specification. The namespace identifier for these faultcode values is "<http://schemas.xmlsoap.org/soap/envelope/>". Use of this space is recommended (but not required) in the specification of methods defined outside of the present specification.

The default SOAP faultcode values are defined in an extensible manner that allows for new SOAP faultcode values to be defined while maintaining backwards compatibility with existing faultcode values. The mechanism used is very similar to the 1xx, 2xx, 3xx etc basic status classes defined in HTTP (see [\[5\]](#) section 10). However, instead of integers, they are defined as XML qualified names (see [\[8\]](#) section 3). The character "." (dot) is used as a separator of faultcode values indicating that what is to the left of the dot is a more generic fault code value than the value to the right. Example

Client.Authentication

The set of faultcode values defined in this document is:

Name	Meaning
VersionMismatch	The processing party found an invalid namespace for the SOAP Envelope element (see section 4.1.2)
MustUnderstand	An immediate child element of the SOAP Header element that was either not understood or not obeyed by the processing party contained a SOAP mustUnderstand attribute with a value of "1" (see section 4.2.3)
	The Client class of errors indicate that the message was incorrectly formed or did not contain the appropriate information in order to succeed. For example, the message

Client	could lack the proper authentication or payment information. It is generally an indication that the message should not be resent without change. See also section 4.4 for a description of the SOAP Fault detail sub-element.
Server	The Server class of errors indicate that the message could not be processed for reasons not directly attributable to the contents of the message itself but rather to the processing of the message. For example, processing could include communicating with an upstream processor, which didn't respond. The message may succeed at a later point in time. See also section 4.4 for a description of the SOAP Fault detail sub-element.

5. SOAP Encoding

The SOAP encoding style is based on a simple type system that is a generalization of the common features found in type systems in programming languages, databases and semi-structured data. A type either is a simple (scalar) type or is a compound type constructed as a composite of several parts, each with a type. This is described in more detail below. This section defines rules for serialization of a graph of typed objects. It operates on two levels. First, given a schema in any notation consistent with the type system described, a schema for an XML grammar may be constructed. Second, given a type-system schema and a particular graph of values conforming to that schema, an XML instance may be constructed. In reverse, given an XML instance produced in accordance with these rules, and given also the original schema, a copy of the original value graph may be constructed.

The namespace identifier for the elements and attributes defined in this section is "<http://schemas.xmlsoap.org/soap/encoding/>". The encoding samples shown assume all namespace declarations are at a higher element level.

Use of the data model and encoding style described in this section is encouraged but not required; other data models and encodings can be used in conjunction with SOAP (see [section 4.1.1](#)).

5.1 Rules for Encoding Types in XML

XML allows very flexible encoding of data. SOAP defines a narrower set of rules for encoding. This section defines the encoding rules at a high level, and the next section describes the encoding rules for specific types when they require more detail. The encodings described in this section can be used in conjunction with the mapping of RPC calls and responses specified in [Section 7](#).

To describe encoding, the following terminology is used:

1. A "value" is a string, the name of a measurement (number, date, enumeration, etc.) or a composite of several such primitive values. All values are of specific types.
2. A "simple value" is one without named parts. Examples of simple values are particular strings, integers, enumerated values etc.
3. A "compound value" is an aggregate of relations to other values. Examples of Compound Values are particular purchase orders, stock reports, street addresses, etc.
4. Within a compound value, each related value is potentially distinguished by a role name, ordinal or both. This is called its "accessor." Examples of compound values include particular Purchase Orders, Stock Reports etc. Arrays are also compound values. It is possible to have compound values with several accessors each named the same, as for example, RDF does.
5. An "array" is a compound value in which ordinal position serves as the only distinction among member values.

6. A "struct" is a compound value in which accessor name is the only distinction among member values, and no accessor has the same name as any other.
7. A "simple type" is a class of simple values. Examples of simple types are the classes called "string," "integer," enumeration classes, etc.
8. A "compound type" is a class of compound values. An example of a compound type is the class of purchase order values sharing the same accessors (shipTo, totalCost, etc.) though with potentially different values (and perhaps further constrained by limits on certain values).
9. Within a compound type, if an accessor has a name that is distinct within that type but is not distinct with respect to other types, that is, the name plus the type together are needed to make a unique identification, the name is called "locally scoped." If however the name is based in part on a Uniform Resource Identifier, directly or indirectly, such that the name alone is sufficient to uniquely identify the accessor irrespective of the type within which it appears, the name is called "universally scoped."
10. Given the information in the schema relative to which a graph of values is serialized, it is possible to determine that some values can only be related by a single instance of an accessor. For others, it is not possible to make this determination. If only one accessor can reference it, a value is considered "single-reference". If referenced by more than one, actually or potentially, it is "multi-reference." Note that it is possible for a certain value to be considered "single-reference" relative to one schema and "multi-reference" relative to another.
11. Syntactically, an element may be "independent" or "embedded." An independent element is any element appearing at the top level of a serialization. All others are embedded elements.

Although it is possible to use the `xsi:type` attribute such that a graph of values is self-describing both in its structure and the types of its values, the serialization rules permit that the types of values MAY be determinate only by reference to a schema. Such schemas MAY be in the notation described by "XML Schema Part 1: Structures" [10] and "XML Schema Part 2: Datatypes" [11] or MAY be in any other notation. Note also that, while the serialization rules apply to compound types other than arrays and structs, many schemas will contain only struct and array types.

The rules for serialization are as follows:

1. All values are represented as element content. A multi-reference value MUST be represented as the content of an independent element. A single-reference value SHOULD not be (but MAY be).
2. For each element containing a value, the type of the value MUST be represented by at least one of the following conditions: (a) the containing element instance contains an `xsi:type` attribute, (b) the containing element instance is itself contained within an element containing a (possibly defaulted) `SOAP-ENC:arrayType` attribute or (c) or the name of the element bears a definite relation to the type, that type then determinable from a schema.
3. A simple value is represented as character data, that is, without any subelements. Every simple value must have a type that is either listed in the XML Schemas Specification, part 2 [11] or whose source type is listed therein (see also [section 5.2](#)).
4. A Compound Value is encoded as a sequence of elements, each accessor represented by an embedded element whose name corresponds to the name of the accessor. Accessors whose names are local to their containing types have unqualified element names; all others have qualified names (see also [section 5.4](#)).
5. A multi-reference simple or compound value is encoded as an independent element containing a local, unqualified attribute named "id" and of type "ID" per the XML Specification [7]. Each accessor to this value is an empty element having a local, unqualified attribute named "href" and of type "uri-reference" per the XML Schema Specification [11], with a "href" attribute value of a URI fragment identifier referencing the corresponding independent element.
6. Strings and byte arrays are represented as multi-reference simple types, but special rules allow them to be represented efficiently for common cases (see also [section 5.2.1](#) and [5.2.3](#)). An accessor to a string or byte-array value MAY have an attribute named "id" and of type "ID" per the XML Specification [7]. If so, all other accessors to the same value are encoded as empty elements having a local, unqualified attribute named "href" and

of type "uri-reference" per the XML Schema Specification [11], with a "href" attribute value of a URI fragment identifier referencing the single element containing the value.

7. It is permissible to encode several references to a value as though these were references to several distinct values, but only when from context it is known that the meaning of the XML instance is unaltered.
8. Arrays are compound values (see also [section 5.4.2](#)). SOAP arrays are defined as having a type of "SOAP-ENC:Array" or a type derived there from.

SOAP arrays have one or more dimensions (rank) whose members are distinguished by ordinal position. An array value is represented as a series of elements reflecting the array, with members appearing in ascending ordinal sequence. For multi-dimensional arrays the dimension on the right side varies most rapidly. Each member element is named as an independent element (see [rule 2](#)).

SOAP arrays can be single-reference or multi-reference values, and consequently may be represented as the content of either an embedded or independent element.

SOAP arrays MUST contain a "SOAP-ENC:arrayType" attribute whose value specifies the type of the contained elements as well as the dimension(s) of the array. The value of the "SOAP-ENC:arrayType" attribute is defined as follows:

```
arrayTypeValue = atype asize
atype           = QName *( rank )
rank           = "[" *( "," ) "]"
asize          = "[" #length "]"
length         = 1 *DIGIT
```

The "atype" construct is the type name of the contained elements expressed as a QName as would appear in the "type" attribute of an XML Schema element declaration and acts as a type constraint (meaning that all values of contained elements are asserted to conform to the indicated type; that is, the type cited in SOAP-ENC:arrayType must be the type or a supertype of every array member). In the case of arrays of arrays or "jagged arrays", the type component is encoded as the "innermost" type name followed by a rank construct for each level of nested arrays starting from 1. Multi-dimensional arrays are encoded using a comma for each dimension starting from 1.

The "asize" construct contains a comma separated list of zero, one, or more integers indicating the lengths of each dimension of the array. A value of zero integers indicates that no particular quantity is asserted but that the size may be determined by inspection of the actual members.

For example, an array with 5 members of type array of integers would have an arrayTypeValue value of "int[] [5]" of which the atype value is "int[]" and the asize value is "[5]". Likewise, an array with 3 members of type two-dimensional arrays of integers would have an arrayTypeValue value of "int[,] [3]" of which the atype value is "int[,] " and the asize value is "[3]".

A SOAP array member MAY contain a "SOAP-ENC:offset" attribute indicating the offset position of that item in the enclosing array. This can be used to indicate the offset position of a partially represented array (see [section 5.4.2.1](#)). Likewise, an array member MAY contain a "SOAP-ENC:position" attribute indicating the position of that item in the enclosing array. This can be used to describe members of sparse arrays (see [section 5.4.2.2](#)). The value of the "SOAP-ENC:offset" and the "SOAP-ENC:position" attribute is defined as follows:

```
arrayPoint = "[" #length "]"
```

with offsets and positions based at 0.

9. A NULL value or a default value MAY be represented by omission of the accessor element. A NULL value MAY also be indicated by an accessor element containing the attribute xsi:null with value '1' or possibly other application-dependent attributes and values.

Note that [rule 2](#) allows independent elements and also elements representing the members of arrays to have names which are not identical to the type of the contained value.

5.2 Simple Types

For simple types, SOAP adopts all the types found in the section "Built-in datatypes" of the "XML Schema Part 2: Datatypes" Specification [11], both the value and lexical spaces. Examples include:

Type	Example
int	58502
float	314159265358979E+1
negativeInteger	-32768
string	Louis "Satchmo" Armstrong

The datatypes declared in the XML Schema specification may be used directly in element schemas. Types derived from these may also be used. An example of a schema fragment and corresponding instance data with elements of these types is:

```
<element name="age" type="int"/>
<element name="height" type="float"/>
<element name="displacement" type="negativeInteger"/>
<element name="color">
  <simpleType base="xsd:string">
    <enumeration value="Green"/>
    <enumeration value="Blue"/>
  </simpleType>
</element>
```

```
<age>45</age>
<height>5.9</height>
<displacement>-450</displacement>
<color>Blue</color>
```

All simple values **MUST** be encoded as the content of elements whose type is either defined in "XML Schema Part 2: Datatypes" Specification [11], or is based on a type found there by using the mechanisms provided in the XML Schema specification.

If a simple value is encoded as an independent element or member of a heterogeneous array it is convenient to have an element declaration corresponding to the datatype. Because the "XML Schema Part 2: Datatypes" Specification [11] includes type definitions but does not include corresponding element declarations, the SOAP-ENC schema and namespace declares an element for every simple datatype. These **MAY** be used.

```
<SOAP-ENC:int id="int1">45</SOAP-ENC:int>
```

5.2.1 Strings

The datatype "string" is defined in "XML Schema Part 2: Datatypes" Specification [11]. Note that this is not identical to the type called "string" in many database or programming languages, and in particular may forbid some characters those languages would permit. (Those values must be represented by using some datatype other than xsd:string.)

A string MAY be encoded as a single-reference or a multi-reference value.

The containing element of the string value MAY have an "id" attribute. Additional accessor elements MAY then have matching "href" attributes.

For example, two accessors to the same string could appear, as follows:

```
<greeting id="String-0">Hello</greeting>
<salutation href="#String-0"/>
```

However, if the fact that both accessors reference the same instance of the string (or subtype of string) is immaterial, they may be encoded as two single-reference values as follows:

```
<greeting>Hello</greeting>
<salutation>Hello</salutation>
```

Schema fragments for these examples could appear similar to the following:

```
<element name="greeting" type="SOAP-ENC:string"/>
<element name="salutation" type="SOAP-ENC:string"/>
```

(In this example, the type SOAP-ENC:string is used as the element's type as a convenient way to declare an element whose datatype is "xsd:string" and which also allows an "id" and "href" attribute. See the SOAP Encoding schema for the exact definition. Schemas MAY use these declarations from the SOAP Encoding schema but are not required to.)

5.2.2 Enumerations

The "XML Schema Part 2: Datatypes" Specification [11] defines a mechanism called "enumeration." The SOAP data model adopts this mechanism directly. However, because programming and other languages often define enumeration somewhat differently, we spell-out the concept in more detail here and describe how a value that is a member of an enumerated list of possible values is to be encoded. Specifically, it is encoded as the name of the value.

"Enumeration" as a concept indicates a set of distinct names. A specific enumeration is a specific list of distinct values appropriate to the base type. For example the set of color names ("Green", "Blue", "Brown") could be defined as an enumeration based on the string built-in type. The values ("1", "3", "5") are a possible enumeration based on integer, and so on. "XML Schema Part 2: Datatypes" [11] supports enumerations for all of the simple types except for boolean. The language of "XML Schema Part 1: Structures" Specification [10] can be used to define enumeration types. If a schema is generated from another notation in which no specific base type is applicable, use "string". In the following schema example "EyeColor" is defined as a string with the possible values of "Green", "Blue", or "Brown" enumerated, and instance data is shown accordingly.

```
<element name="EyeColor" type="tns:EyeColor"/>
<simpleType name="EyeColor" base="xsd:string">
  <enumeration value="Green"/>
  <enumeration value="Blue"/>
  <enumeration value="Brown"/>
</simpleType>
```

```
<Person>
  <Name>Henry Ford</Name>
  <Age>32</Age>
  <EyeColor>Brown</EyeColor>
</Person>
```

5.2.3 Array of Bytes

An array of bytes MAY be encoded as a single-reference or a multi-reference value. The rules for an array of bytes are similar to those for a string.

In particular, the containing element of the array of bytes value MAY have an "id" attribute. Additional accessor elements MAY then have matching "href" attributes.

The recommended representation of an opaque array of bytes is the 'base64' encoding defined in XML Schemas [10] [11], which uses the base64 encoding algorithm defined in 2045 [13]. However, the line length restrictions that normally apply to base64 data in MIME do not apply in SOAP. A "SOAP-ENC:base64" subtype is supplied for use with SOAP.

```
<picture xsi:type="SOAP-ENC:base64">
  aG93IG5vDyBicm73biBjb3cNCg==
</picture>
```

5.3 Polymorphic Accessor

Many languages allow accessors that can polymorphically access values of several types, each type being available at run time. A polymorphic accessor instance MUST contain an "xsi:type" attribute that describes the type of the actual value.

For example, a polymorphic accessor named "cost" with a value of type "xsd:float" would be encoded as follows:

```
<cost xsi:type="xsd:float">29.95</cost>
```

as contrasted with a cost accessor whose value's type is invariant, as follows:

```
<cost>29.95</cost>
```

5.4 Compound types

SOAP defines types corresponding to the following structural patterns often found in programming languages:

Struct

A "struct" is a compound value in which accessor name is the only distinction among member values, and no accessor has the same name as any other.

Array

An "array" is a compound value in which ordinal position serves as the only distinction among member values.

SOAP also permits serialization of data that is neither a Struct nor an Array, for example data such as is found in a Directed-Labeled-Graph Data Model in which a single node has many distinct accessors, some of which occur more than once. SOAP serialization does not require that the underlying data model make an ordering distinction among accessors, but if such an order exists, the accessors MUST be encoded in that sequence.

5.4.1 Compound Values, Structs and References to Values

The members of a Compound Value are encoded as accessor elements. When accessors are distinguished by their name (as for example in a struct), the accessor name is used as the element name. Accessors whose names are local to their containing types have unqualified element names; all others have qualified names.

The following is an example of a struct of type "Book":

```
<e:Book>
  <author>Henry Ford</author>
  <preface>Prefatory text</preface>
  <intro>This is a book.</intro>
</e:Book>
```

And this is a schema fragment describing the above structure:

```
<element name="Book">
  <complexType>
    <element name="author" type="xsd:string"/>
    <element name="preface" type="xsd:string"/>
    <element name="intro" type="xsd:string"/>
  </complexType>
</e:Book>
```

Below is an example of a type with both simple and complex members. It shows two levels of referencing. Note that the "href" attribute of the "Author" accessor element is a reference to the value whose "id" attribute matches. A similar construction appears for the "Address".

```
<e:Book>
  <title>My Life and Work</title>
  <author href="#Person-1"/>
</e:Book>
<e:Person id="Person-1">
  <name>Henry Ford</name>
  <address href="#Address-2"/>
</e:Person>
<e:Address id="Address-2">
  <email>mailto:henryford@hotmail.com</email>
  <web>http://www.henryford.com</web>
</e:Address>
```

The form above is appropriate when the "Person" value and the "Address" value are multi-reference. If these were instead both single-reference, they SHOULD be embedded, as follows:

```
<e:Book>
  <title>My Life and Work</title>
  <author>
    <name>Henry Ford</name>
    <address>
      <email>mailto:henryford@hotmail.com</email>
      <web>http://www.henryford.com</web>
    </address>
  </author>
</e:Book>
```

If instead there existed a restriction that no two persons can have the same address in a given instance and that an address can be either a Street-address or an Electronic-address, a Book with two authors would be encoded as follows:

```
<e:Book>
  <title>My Life and Work</title>
```

```

<firstauthor href="#Person-1"/>
<secondauthor href="#Person-2"/>
</e:Book>
<e:Person id="Person-1">
  <name>Henry Ford</name>
  <address xsi:type="m:Electronic-address">
    <email>mailto:henryford@hotmail.com</email>
    <web>http://www.henryford.com</web>
  </address>
</e:Person>
<e:Person id="Person-2">
  <name>Samuel Crowther</name>
  <address xsi:type="n:Street-address">
    <street>Martin Luther King Rd</street>
    <city>Raleigh</city>
    <state>North Carolina</state>
  </address>
</e:Person>

```

Serializations can contain references to values not in the same resource:

```

<e:Book>
  <title>Paradise Lost</title>
  <firstauthor href="http://www.dartmouth.edu/~milton/">
</e:Book>

```

And this is a schema fragment describing the above structures:

```

<element name="Book" type="tns:Book"/>
<complexType name="Book">
  <!-- Either the following group must occur or else the
    href attribute must appear, but not both. -->
  <sequence minOccurs="0" maxOccurs="1">
    <element name="title" type="xsd:string"/>
    <element name="firstauthor" type="tns:Person"/>
    <element name="secondauthor" type="tns:Person"/>
  </sequence>
  <attribute name="href" type="uriReference"/>
  <attribute name="id" type="ID"/>
  <anyAttribute namespace="##other"/>
</complexType>

```

```

<element name="Person" base="tns:Person"/>
<complexType name="Person">
  <!-- Either the following group must occur or else the
    href attribute must appear, but not both. -->
  <sequence minOccurs="0" maxOccurs="1">
    <element name="name" type="xsd:string"/>
    <element name="address" type="tns:Address"/>
  </sequence>
  <attribute name="href" type="uriReference"/>
  <attribute name="id" type="ID"/>
  <anyAttribute namespace="##other"/>
</complexType>

```

```

<element name="Address" base="tns:Address"/>
<complexType name="Address">
  <!-- Either the following group must occur or else the
       href attribute must appear, but not both. -->
  <sequence minOccurs="0" maxOccurs="1">
    <element name="street" type="xsd:string"/>
    <element name="city" type="xsd:string"/>
    <element name="state" type="xsd:string"/>
  </sequence>
  <attribute name="href" type="uriReference"/>
  <attribute name="id" type="ID"/>
  <anyAttribute namespace="##other"/>
</complexType>

```

5.4.2 Arrays

SOAP arrays are defined as having a type of "SOAP-ENC:Array" or a type derived there from (see also [rule 8](#)). Arrays are represented as element values, with no specific constraint on the name of the containing element (just as values generally do not constrain the name of their containing element).

Arrays can contain elements which themselves can be of any type, including nested arrays. New types formed by restrictions of SOAP-ENC:Array can also be created to represent, for example, arrays limited to integers or arrays of some user-defined enumeration.

The representation of the value of an array is an ordered sequence of elements constituting the items of the array. Within an array value, element names are not significant for distinguishing accessors. Elements may have any name. In practice, elements will frequently be named so that their declaration in a schema suggests or determines their type. As with compound types generally, if the value of an item in the array is a single-reference value, the item contains its value. Otherwise, the item references its value via an "href" attribute.

The following example is a schema fragment and an array containing integer array members.

```

<element name="myFavoriteNumbers"
  type="SOAP-ENC:Array"/>

<myFavoriteNumbers
  SOAP-ENC:arrayType="xsd:int[2]">
  <number>3</number>
  <number>4</number>
</myFavoriteNumbers>

```

In that example, the array "myFavoriteNumbers" contains several members each of which is a value of type SOAP-ENC:int. This can be determined by inspection of the SOAP-ENC:arrayType attribute. Note that the SOAP-ENC:Array type allows unqualified element names without restriction. These convey no type information, so when used they must either have an xsi:type attribute or the containing element must have a SOAP-ENC:arrayType attribute. Naturally, types derived from SOAP-ENC:Array may declare local elements, with type information.

As previously noted, the SOAP-ENC schema contains declarations of elements with names corresponding to each simple type in the "XML Schema Part 2: Datatypes" Specification [11]. It also contains a declaration for "Array". Using these, we might write

```

<SOAP-ENC:Array SOAP-ENC:arrayType="xsd:int[2]">
  <SOAP-ENC:int>3</SOAP-ENC:int>

```

```
<SOAP-ENC:int>4</SOAP-ENC:int>
</SOAP-ENC:Array>
```

Arrays can contain instances of any subtype of the specified arrayType. That is, the members may be of any type that is substitutable for the type specified in the arrayType attribute, according to whatever substitutability rules are expressed in the schema. So, for example, an array of integers can contain any type derived from integer (for example "int" or any user-defined derivation of integer). Similarly, an array of "address" might contain a restricted or extended type such as "internationalAddress". Because the supplied SOAP-ENC:Array type admits members of any type, arbitrary mixtures of types can be contained unless specifically limited by use of the arrayType attribute.

Types of member elements can be specified using the xsi:type attribute in the instance, or by declarations in the schema of the member elements, as the following two arrays demonstrate respectively.

```
<SOAP-ENC:Array SOAP-ENC:arrayType="xsd:ur-type[4]">
  <thing xsi:type="xsd:int">12345</thing>
  <thing xsi:type="xsd:decimal">6.789</thing>
  <thing xsi:type="xsd:string">
    Of Mans First Disobedience, and the Fruit
    Of that Forbidden Tree, whose mortal tast
    Brought Death into the World, and all our woe,
  </thing>
  <thing xsi:type="xsd:uriReference">
    http://www.dartmouth.edu/~milton/reading_room/
  </thing>
</SOAP-ENC:Array>
```

```
<SOAP-ENC:Array SOAP-ENC:arrayType="xsd:ur-type[4]">
  <SOAP-ENC:int>12345</SOAP-ENC:int>
  <SOAP-ENC:decimal>6.789</SOAP-ENC:decimal>
  <xsd:string>
    Of Mans First Disobedience, and the Fruit
    Of that Forbidden Tree, whose mortal tast
    Brought Death into the World, and all our woe,
  </xsd:string>
  <SOAP-ENC:uriReference>
    http://www.dartmouth.edu/~milton/reading_room/
  </SOAP-ENC:uriReference>
</SOAP-ENC:Array>
```

Array values may be structs or other compound values. For example an array of "xyz:Order" structs :

```
<SOAP-ENC:Array SOAP-ENC:arrayType="xyz:Order[2]">
  <Order>
    <Product>Apple</Product>
    <Price>1.56</Price>
  </Order>
  <Order>
    <Product>Peach</Product>
    <Price>1.48</Price>
  </Order>
</SOAP-ENC:Array>
```

Arrays may have other arrays as member values. The following is an example of an array of two arrays, each of which is an array of strings.

```

<SOAP-ENC:Array SOAP-ENC:arrayType="xsd:string[][2]">
  <item href="#array-1"/>
  <item href="#array-2"/>
</SOAP-ENC:Array>
<SOAP-ENC:Array id="array-1" SOAP-ENC:arrayType="xsd:string[2]">
  <item>r1c1</item>
  <item>r1c2</item>
  <item>r1c3</item>
</SOAP-ENC:Array>
<SOAP-ENC:Array id="array-2" SOAP-ENC:arrayType="xsd:string[2]">
  <item>r2c1</item>
  <item>r2c2</item>
</SOAP-ENC:Array>

```

The element containing an array value does not need to be named "SOAP-ENC:Array". It may have any name, provided that the type of the element is either SOAP-ENC:Array or is derived from SOAP-ENC:Array by restriction. For example, the following is a fragment of a schema and a conforming instance array.

```

<simpleType name="phoneNumber" base="string"/>

<element name="ArrayOfPhoneNumbers">
  <complexType base="SOAP-ENC:Array">
    <element name="phoneNumber" type="tns:phoneNumber" maxOccurs="unbounded"/>
  </complexType>
  <anyAttribute/>
</element>

<xyz:ArrayOfPhoneNumbers SOAP-ENC:arrayType="xyz:phoneNumber[2]">
  <phoneNumber>206-555-1212</phoneNumber>
  <phoneNumber>1-888-123-4567</phoneNumber>
</xyz:ArrayOfPhoneNumbers>

```

Arrays may be multi-dimensional. In this case, more than one size will appear within the asize part of the arrayType attribute:

```

<SOAP-ENC:Array SOAP-ENC:arrayType="xsd:string[2,3]">
  <item>r1c1</item>
  <item>r1c2</item>
  <item>r1c3</item>
  <item>r2c1</item>
  <item>r2c2</item>
  <item>r2c3</item>
</SOAP-ENC:Array>

```

While the examples above have shown arrays encoded as independent elements, array values MAY also appear embedded and SHOULD do so when they are known to be single reference.

The following is an example of a schema fragment and an array of phone numbers embedded in a struct of type "Person" and accessed through the accessor "phone-numbers":

```

<simpleType name="phoneNumber" base="string"/>

<element name="ArrayOfPhoneNumbers">
  <complexType base="SOAP-ENC:Array">

```



```

    <element name="phoneNumber" type="tns:phoneNumber" maxOccurs="unbounded"/>
  </complexType>
</anyAttribute/>
</element>

<element name="Person">
  <complexType>
    <element name="name" type="string"/>
    <element name="phoneNumbers" type="tns:ArrayOfPhoneNumbers"/>
  </complexType>
</element>

<xyz:Person>
  <name>John Hancock</name>
  <phoneNumbers SOAP-ENC:arrayType="xyz:phoneNumber[2]">
    <phoneNumber>206-555-1212</phoneNumber>
    <phoneNumber>1-888-123-4567</phoneNumber>
  </phoneNumbers>
</xyz:Person>

```

Here is another example of a single-reference array value encoded as an embedded element whose containing element name is the accessor name:

```

<xyz:PurchaseOrder>
  <CustomerName>Henry Ford</CustomerName>
  <ShipTo>
    <Street>5th Ave</Street>
    <City>New York</City>
    <State>NY</State>
    <Zip>10010</Zip>
  </ShipTo>
  <PurchaseLineItems SOAP-ENC:arrayType="Order[2]">
    <Order>
      <Product>Apple</Product>
      <Price>1.56</Price>
    </Order>
    <Order>
      <Product>Peach</Product>
      <Price>1.48</Price>
    </Order>
  </PurchaseLineItems>
</xyz:PurchaseOrder>

```

5.4.2.1 Partially Transmitted Arrays

SOAP provides support for partially transmitted arrays, known as "varying" arrays in some contexts [12]. A partially transmitted array indicates in an "SOAP-ENC:offset" attribute the zero-origin offset of the first element transmitted. If omitted, the offset is taken as zero.

The following is an example of an array of size five that transmits only the third and fourth element counting from zero:

```

<SOAP-ENC:Array SOAP-ENC:arrayType="xsd:string[5]" SOAP-ENC:offset="[2]">
  <item>The third element</item>

```

```
<item>The fourth element</item>
</SOAP-ENC:Array>
```

5.4.2.2 Sparse Arrays

SOAP provides support for sparse arrays. Each element representing a member value contains a "SOAP-ENC:position" attribute that indicates its position within the array. The following is an example of a sparse array of two-dimensional arrays of strings. The size is 4 but only position 2 is used:

```
<SOAP-ENC:Array SOAP-ENC:arrayType="xsd:string[,] [4]">
  <SOAP-ENC:Array href="#array-1" SOAP-ENC:position="[2]" />
</SOAP-ENC:Array>
<SOAP-ENC:Array id="array-1" SOAP-ENC:arrayType="xsd:string[10,10]">
  <item SOAP-ENC:position="[2,2]">Third row, third col</item>
  <item SOAP-ENC:position="[7,2]">Eighth row, third col</item>
</SOAP-ENC:Array>
```

If the only reference to array-1 occurs in the enclosing array, this example could also have been encoded as follows:

```
<SOAP-ENC:Array SOAP-ENC:arrayType="xsd:string[,] [4]">
  <SOAP-ENC:Array SOAP-ENC:position="[2]" SOAP-ENC:arrayType="xsd:string[10,10]">
    <item SOAP-ENC:position="[2,2]">Third row, third col</item>
    <item SOAP-ENC:position="[7,2]">Eighth row, third col</item>
  </SOAP-ENC:Array>
</SOAP-ENC:Array>
```

5.4.3 Generic Compound Types

The encoding rules just cited are not limited to those cases where the accessor names are known in advance. If accessor names are known only by inspection of the immediate values to be encoded, the same rules apply, namely that the accessor is encoded as an element whose name matches the name of the accessor, and the accessor either contains or references its value. Accessors containing values whose types cannot be determined in advance **MUST** always contain an appropriate xsi:type attribute giving the type of the value.

Similarly, the rules cited are sufficient to allow serialization of compound types having a mixture of accessors distinguished by name and accessors distinguished by both name and ordinal position. (That is, having some accessors repeated.) This does not require that any schema actually contain such types, but rather says that if a type-model schema does have such types, a corresponding XML syntactic schema and instance may be generated.

```
<xyz:PurchaseOrder>
  <CustomerName>Henry Ford</CustomerName>
  <ShipTo>
    <Street>5th Ave</Street>
    <City>New York</City>
    <State>NY</State>
    <Zip>10010</Zip>
  </ShipTo>
  <PurchaseLineItems>
    <Order>
      <Product>Apple</Product>
      <Price>1.56</Price>
    </Order>
    <Order>
      <Product>Peach</Product>
```

```

    <Price>1.48</Price>
  </Order>
</PurchaseLineItems>
</xyz:PurchaseOrder>

```

Similarly, it is valid to serialize a compound value that structurally resembles an array but is not of type (or subtype) SOAP-ENC:Array. For example:

```

<PurchaseLineItems>
  <Order>
    <Product>Apple</Product>
    <Price>1.56</Price>
  </Order>
  <Order>
    <Product>Peach</Product>
    <Price>1.48</Price>
  </Order>
</PurchaseLineItems>

```

5.5 Default Values

An omitted accessor element implies either a default value or that no value is known. The specifics depend on the accessor, method, and its context. For example, an omitted accessor typically implies a Null value for polymorphic accessors (with the exact meaning of Null accessor-dependent). Likewise, an omitted Boolean accessor typically implies either a False value or that no value is known, and an omitted numeric accessor typically implies either that the value is zero or that no value is known.

5.6 SOAP root Attribute

The SOAP root attribute can be used to label serialization roots that are not true roots of an object graph so that the object graph can be deserialized. The attribute can have one of two values, either "1" or "0". True roots of an object graph have the implied attribute value of "1". Serialization roots that are not true roots can be labeled as serialization roots with an attribute value of "1". An element can explicitly be labeled as not being a serialization root with a value of "0".

The SOAP root attribute MAY appear on any subelement within the SOAP Header and SOAP Body elements. The attribute does not have a default value.

6. Using SOAP in HTTP

This section describes how to use SOAP within HTTP with or without using the HTTP Extension Framework. Binding SOAP to HTTP provides the advantage of being able to use the formalism and decentralized flexibility of SOAP with the rich feature set of HTTP. Carrying SOAP in HTTP does not mean that SOAP overrides existing semantics of HTTP but rather that the semantics of SOAP over HTTP maps naturally to HTTP semantics.

SOAP naturally follows the HTTP request/response message model providing SOAP request parameters in a HTTP request and SOAP response parameters in a HTTP response. Note, however, that SOAP intermediaries are NOT the same as HTTP intermediaries. That is, an HTTP intermediary addressed with the HTTP Connection header field cannot be expected to inspect or process the SOAP entity body carried in the HTTP request.

HTTP applications MUST use the media type "text/xml" according to RFC 2376 [3] when including SOAP entity bodies in HTTP messages.

6.1 SOAP HTTP Request

Although SOAP might be used in combination with a variety of HTTP request methods, this binding only defines SOAP within HTTP POST requests (see [section 7](#) for how to use SOAP for RPC and [section 6.3](#) for how to use the HTTP Extension Framework).

6.1.1 The SOAPAction HTTP Header Field

The SOAPAction HTTP request header field can be used to indicate the intent of the SOAP HTTP request. The value is a URI identifying the intent. SOAP places no restrictions on the format or specificity of the URI or that it is resolvable. An HTTP client **MUST** use this header field when issuing a SOAP HTTP Request.

```
soapaction      = "SOAPAction" ":" [ "<"> URI-reference ">" ]  
URI-reference = <as defined in RFC 2396 [4]>
```

The presence and content of the SOAPAction header field can be used by servers such as firewalls to appropriately filter SOAP request messages in HTTP. The header field value of empty string ("") means that the intent of the SOAP message is provided by the HTTP Request-URI. No value means that there is no indication of the intent of the message.

Examples:

```
SOAPAction: "http://electrocommerce.org/abc#MyMessage"  
SOAPAction: "myapp.sdl"  
SOAPAction: ""  
SOAPAction:
```

6.2 SOAP HTTP Response

SOAP HTTP follows the semantics of the HTTP Status codes for communicating status information in HTTP. For example, a 2xx status code indicates that the client's request including the SOAP component was successfully received, understood, and accepted etc.

In case of a SOAP error while processing the request, the SOAP HTTP server **MUST** issue an HTTP 500 "Internal Server Error" response and include a SOAP message in the response containing a SOAP Fault element (see [section 4.4](#)) indicating the SOAP processing error.

6.3 The HTTP Extension Framework

A SOAP message **MAY** be used together with the HTTP Extension Framework [6] in order to identify the presence and intent of a SOAP HTTP request.

Whether to use the Extension Framework or plain HTTP is a question of policy and capability of the communicating parties. Clients can force the use of the HTTP Extension Framework by using a mandatory extension declaration and the "M-" HTTP method name prefix. Servers can force the use of the HTTP Extension Framework by using the 510 "Not Extended" HTTP status code. That is, using one extra round trip, either party can detect the policy of the other party and act accordingly.

The extension identifier used to identify SOAP using the Extension Framework is

```
http://schemas.xmlsoap.org/soap/envelope/
```

6.4 SOAP HTTP Examples

Example 3 SOAP HTTP Using POST

```
POST /StockQuote HTTP/1.1
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
SOAPAction: "http://electrocommerce.org/abc#MyMessage"

<SOAP-ENV:Envelope...

HTTP/1.1 200 OK
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn

<SOAP-ENV:Envelope...
```

Example 4 SOAP Using HTTP Extension Framework

```
M-POST /StockQuote HTTP/1.1
Man: "http://schemas.xmlsoap.org/soap/envelope/"; ns=NNNN
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
NNNN-SOAPAction: "http://electrocommerce.org/abc#MyMessage"

<SOAP-ENV:Envelope...

HTTP/1.1 200 OK
Ext:
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn

<SOAP-ENV:Envelope...
```

7. Using SOAP for RPC

One of the design goals of SOAP is to encapsulate and exchange RPC calls using the extensibility and flexibility of XML. This section defines a uniform representation of remote procedure calls and responses.

Although it is anticipated that this representation is likely to be used in combination with the encoding style defined in [section 5](#) other representations are possible. The SOAP encodingStyle attribute (see [section 4.3.2](#)) can be used to indicate the encoding style of the method call and or the response using the representation described in this section.

Using SOAP for RPC is orthogonal to the SOAP protocol binding (see [section 6](#)). In the case of using HTTP as the protocol binding, an RPC call maps naturally to an HTTP request and an RPC response maps to an HTTP response. However, using SOAP for RPC is not limited to the HTTP protocol binding.

To make a method call, the following information is needed:

- The URI of the target object
- A method name

- An optional method signature
- The parameters to the method
- Optional header data

SOAP relies on the protocol binding to provide a mechanism for carrying the URI. For example, for HTTP the request URI indicates the resource that the invocation is being made against. Other than it be a valid URI, SOAP places no restriction on the form of an address (see [4] for more information on URIs).

7.1 RPC and SOAP Body

RPC method calls and responses are both carried in the SOAP Body element (see [section 4.3](#)) using the following representation:

- A method invocation is modelled as a struct.
- The method invocation is viewed as a single struct containing an accessor for each [in] or [in/out] parameter. The struct is both named and typed identically to the method name.
- Each [in] or [in/out] parameter is viewed as an accessor, with a name corresponding to the name of the parameter and type corresponding to the type of the parameter. These appear in the same order as in the method signature.
- A method response is modelled as a struct.
- The method response is viewed as a single struct containing an accessor for the return value and each [out] or [in/out] parameter. The first accessor is the return value followed by the parameters in the same order as in the method signature.
- Each parameter accessor has a name corresponding to the name of the parameter and type corresponding to the type of the parameter. The name of the return value accessor is not significant. Likewise, the name of the struct is not significant. However, a convention is to name it after the method name with the string "Response" appended.
- A method fault is encoded using the SOAP Fault element (see [section 4.4](#)). If a protocol binding adds additional rules for fault expression, those also MUST be followed.

As noted above, method and response structs can be encoded according to the rules in [section 5](#), or other encodings can be specified using the `encodingStyle` attribute (see [section 4.1.1](#)).

Applications MAY process requests with missing parameters but also MAY return a fault.

Because a result indicates success and a fault indicates failure, it is an error for the method response to contain both a result and a fault.

7.2 RPC and SOAP Header

Additional information relevant to the encoding of a method request but not part of the formal method signature MAY be expressed in the RPC encoding. If so, it MUST be expressed as a subelement of the SOAP Header element.

An example of the use of the header element is the passing of a transaction ID along with a message. Since the transaction ID is not part of the signature and is typically held in an infrastructure component rather than application code, there is no direct way to pass the necessary information with the call. By adding an entry to the headers and giving it a fixed name, the transaction manager on the receiving side can extract the transaction ID and use it without affecting the coding of remote procedure calls.

8. Security Considerations

Not described in this document are methods for integrity and privacy protection. Such issues will be addressed more fully in a future version(s) of this document.

9. References

- [1] S. Bradner, "The Internet Standards Process -- Revision 3", [RFC2026](#), Harvard University, October 1996
- [2] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), Harvard University, March 1997
- [3] E. Whitehead, M. Murata, "XML Media Types", [RFC2376](#), UC Irvine, Fuji Xerox Info. Systems, July 1998
- [4] T. Berners-Lee, R. Fielding, L. Masinter, "Uniform Resource Identifiers (URI): Generic Syntax", [RFC 2396](#), MIT/LCS, U.C. Irvine, Xerox Corporation, August 1998.
- [5] R. Fielding, J. Gettys, J. C. Mogul, H. Frystyk, T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), U.C. Irvine, DEC W3C/MIT, DEC, W3C/MIT, W3C/MIT, January 1997
- [6] H. Nielsen, P. Leach, S. Lawrence, "An HTTP Extension Framework", [RFC 2774](#), Microsoft, Microsoft, Agranat Systems
- [7] W3C Recommendation "[The XML Specification](#)"
- [8] W3C Recommendation "[Namespaces in XML](#)"
- [9] W3C Working Draft "[XML Linking Language](#)". This is work in progress.
- [10] W3C Working Draft "[XML Schema Part 1: Structures](#)". This is work in progress.
- [11] W3C Working Draft "[XML Schema Part 2: Datatypes](#)". This is work in progress.
- [12] Transfer Syntax NDR, in "[DCE 1.1: Remote Procedure Call](#)"
- [13] N. Freed, N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", [RFC2045](#), Innosoft, First Virtual, November 1996

A. SOAP Envelope Examples

A.1 Sample Encoding of Call Requests

Example 5 Similar to [Example 1](#) but with a Mandatory Header

```
POST /StockQuote HTTP/1.1
Host: www.stockquoteserver.com
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
SOAPAction: "Some-URI"
```

```

<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Header>
    <t:Transaction
      xmlns:t="some-URI"
      SOAP-ENV:mustUnderstand="1">
      5
    </t:Transaction>
  </SOAP-ENV:Header>
  <SOAP-ENV:Body>
    <m:GetLastTradePrice xmlns:m="Some-URI">
      <symbol>DEF</symbol>
    </m:GetLastTradePrice>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

Example 6 Similar to Example 1 but with multiple request parameters

```

POST /StockQuote HTTP/1.1
Host: www.stockquoteserver.com
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
SOAPAction: "Some-URI"

```

```

<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <m:GetLastTradePriceDetailed
      xmlns:m="Some-URI">
      <Symbol>DEF</Symbol>
      <Company>DEF Corp</Company>
      <Price>34.1</Price>
    </m:GetLastTradePriceDetailed>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

A.2 Sample Encoding of Response

Example 7 Similar to Example 2 but with a Mandatory Header

```

HTTP/1.1 200 OK
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn

```

```

<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Header>
    <t:Transaction

```



```

        xmlns:t="some-URI"
        xsi:type="xsd:int" mustUnderstand="1">
    5
    </t:Transaction>
</SOAP-ENV:Header>
<SOAP-ENV:Body>
    <m:GetLastTradePriceResponse
        xmlns:m="Some-URI">
        <Price>34.5</Price>
    </m:GetLastTradePriceResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

Example 8 Similar to Example 2 but with a Struct

```

HTTP/1.1 200 OK
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn

<SOAP-ENV:Envelope
    xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
    SOAP-ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
    <SOAP-ENV:Body>
        <m:GetLastTradePriceResponse
            xmlns:m="Some-URI">
            <PriceAndVolume>
                <LastTradePrice>
                    34.5
                </LastTradePrice>
                <DayVolume>
                    10000
                </DayVolume>
            </PriceAndVolume>
        </m:GetLastTradePriceResponse>
    </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

Example 9 Similar to Example 2 but Failing to honor Mandatory Header

```

HTTP/1.1 500 Internal Server Error
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn

<SOAP-ENV:Envelope
    xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/">
    <SOAP-ENV:Body>
        <SOAP-ENV:Fault>
            <faultcode>SOAP-ENV:MustUnderstand</faultcode>
            <faultstring>SOAP Must Understand Error</faultstring>
        </SOAP-ENV:Fault>
    </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

Example 10 Similar to Example 2 but Failing to handle Body

```
HTTP/1.1 500 Internal Server Error
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn

<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/">
  <SOAP-ENV:Body>
    <SOAP-ENV:Fault>
      <faultcode>SOAP-ENV:Server</faultcode>
      <faultstring>Server Error</faultstring>
      <detail>
        <e:myfaultdetails xmlns:e="Some-URI">
          <message>
            My application didn't work
          </message>
          <errorcode>
            1001
          </errorcode>
        </e:myfaultdetails>
      </detail>
    </SOAP-ENV:Fault>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```
